

# RANGER 1000 Premium Polaris Blue

**RANGER**



## Key Specifications

**61**  
HP

**3**  
PERSON CAPACITY

**12.5"**  
GROUND CLEARANCE

## Engine & Drivetrain

Cooling	Liquid
Cylinders Displacement	999cc
Drive System Type	High Performance On-Demand True AWD/2WD/VersaTrac Turf Mode
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke Twin Cylinder SOHC
Fuel System/Battery	Electronic Fuel Injection
Horsepower	61 HP
Transmission/Final Drive	Automatic PVT H/L/N/R/P; Shaft

## Dimensions

Bed Box Dimensions (L x W x H)	36.75 x 54.25 x 12.5 in (93.3 x 137.8 x 31.75 cm)
Box Capacity	1,000 lb (453.6 kg)
Dry Weight	1,485 lb (673.6 kg)
Fuel Capacity	11.35 gal (43 L)
Ground Clearance	12.5 in (31.8 cm)
Hitch Towing Rating	2,500 lb (1,133.9 kg)
Hitch Type	Standard 2 in (5.08 cm) Receiver
Overall Vehicle Size (L x W x H)	120 x 62.5 x 76 in. (305 x 158 x 193 cm)
Payload Capacity	1,500 lb (680.4 kg)
Person Capacity	3
Wheelbase	81 in (206 cm)

## Brakes

<b>Front/Rear Brakes</b>	4-Wheel Hydraulic Disc with Dual-Bore Front and Rear Calipers
<b>Parking Brake</b>	Park In-Transmission

## Additional Specifications

<b>Adjustable Driver Seat</b>	Standard
<b>Cargo System</b>	Lock & Ride
<b>Color / Graphics</b>	Polaris Blue
<b>Electronic Power Steering</b>	Standard
<b>Instrumentation</b>	4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter,  Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet
<b>Lighting</b>	Halogen Headlamps, 55W Low Beam, 60W High Beam, Dual LED Taillamps
<b>Other Standard Features</b>	Polaris Pulse Electrical System (3 position), Standard In-Dash SAE Charge Port
<b>Tilt Steering</b>	Standard

## Tires / Wheels

<b>Front Tires</b>	26 x 9-12; PXT 2.0
<b>Rear Tires</b>	26 x 11-12; PXT 2.0
<b>Tire Ply Rating</b>	6 Ply Rated
<b>Wheels</b>	Aluminum Black Xcelerator 2.0

## Suspension

<b>Front Suspension</b>	Dual A-Arm 10 in. (25.4 cm) Travel
<b>Rear Suspension</b>	Dual A-Arm, IRS 10 in (25.4 cm) Travel
<b>Turning Radius</b>	13.3 ft