

# RANGER SP 570 Premium Polaris Blue

**RANGER**



## Key Specifications

**44**  
HP

**56"**  
WIDTH

**11"**  
GROUND CLEARANCE

## Engine & Drivetrain

Cooling	Liquid
Cylinders Displacement	567cc
Drive System Type	On-Demand True AWD/2WD/VersaTrac Turf Mode
Engine Braking System (EBS)	Not Equipped
Engine Type	4-Stroke Single Cylinder DOHC
Fuel System/Battery	Electronic Fuel Injection
Horsepower	44 HP
Transmission/Final Drive	Automatic PVT H/L/N/R/P; Shaft

## Dimensions

Bed Box Dimensions (L x W x H)	33.3 x 48.7 x 12.3 in
Box Capacity	500 lb (230 kg)
Dry Weight	1,245 lbs.
Fuel Capacity	9.5 gal (35.9 L)
Ground Clearance	11 in (27.9 cm)
GVW	2,255 lbs.
Hitch Towing Rating	1,500 lb (680 kg)
Hitch Type	Standard 2 in (5.08 cm) Receiver
Overall Vehicle Size (L x W x H)	108 x 56 x 74 in. (274.3 x 142.2 x 188 cm)
Payload Capacity	925 lbs. (420 kg)
Person Capacity	2
Wheelbase	73 in (185.4 cm)

## Brakes

<b>Front/Rear Brakes</b>	4-Wheel Hydraulic Disc
<b>Parking Brake</b>	Park In-Transmission

## Additional Specifications

<b>Adjustable Driver Seat</b>	Not Equipped
<b>Cargo System</b>	Lock & Ride
<b>Color / Graphics</b>	Polaris Blue
<b>Electronic Power Steering</b>	Standard
<b>Instrumentation</b>	4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet
<b>Lighting</b>	Halogen Headlamps, 55W low beam, 60W high beam, LED Taillamps
<b>Other Standard Features</b>	Premium Cut & Sew Seats, Polaris Pulse Electrical System (3 position), Standard In-Dash SAE Charge Port
<b>Tilt Steering</b>	Standard

## Tires / Wheels

<b>Front Tires</b>	25 x 8-12; Carlisle 489
<b>Rear Tires</b>	25 x 10-12; Carlisle 489
<b>Tire Ply Rating</b>	4 Ply Rated
<b>Wheels</b>	12" Black Aluminum

## Suspension

<b>Front Suspension</b>	MacPherson Strut 9 in (22.9 cm) Travel
<b>Rear Suspension</b>	Dual A-Arm, IRS 10 in (25.4 cm) Travel
<b>Turning Radius</b>	12.7 ft