RANGER SP 570 Premium Polaris Pursuit Camo





| Key Specifications | | | |
|--------------------|-------|------------------|--|
| 44 | 56" | 11" | |
| HP | WIDTH | GROUND CLEARANCE | |
| | | | |

Engine & Drivetrain

| Cooling | Liquid |
|-----------------------------|--|
| Cylinders Displacement | 567cc |
| Drive System Type | On-Demand True AWD/2WD/VersaTrac Turf Mode |
| Engine Braking System (EBS) | Not Equipped |
| Engine Type | 4-Stroke Single Cylinder DOHC |
| Fuel System/Battery | Electronic Fuel Injection |
| Horsepower | 44 HP |
| Transmission/Final Drive | Automatic PVT H/L/N/R/P; Shaft |

Dimensions

| Bed Box Dimensions (L x W x H) | 33.3 x 48.7 x 12.3 in |
|----------------------------------|--|
| Box Capacity | 500 lb (226.8 kg) |
| Dry Weight | 1,245 lbs. |
| Fuel Capacity | 9.5 gal (35.9 L) |
| Ground Clearance | 11 in (27.9 cm) |
| GVW | 2,255 lbs. |
| Hitch Towing Rating | 1,500 lb (680 kg) |
| Hitch Type | Standard 2 in (5.08 cm) Receiver |
| Overall Vehicle Size (L x W x H) | 108 x 56 x 74 in. (274.3 x 142.2 x 188 cm) |
| Payload Capacity | 925 lbs. (420 kg) |
| Person Capacity | 2 |
| Wheelbase | 73 in (185.4 cm) |
| | |

Brakes

| Front/Rear Brakes | 4-Wheel Hydraulic Disc |
|-------------------|------------------------|
| Parking Brake | Park In-Transmission |

Additional Specifications

| Adjustable Driver Seat | Not Equipped |
|---------------------------|---|
| Cargo System | Lock & Ride |
| Color / Graphics | Polaris Pursuit Camo |
| Electronic Power Steering | Standard |
| Instrumentation | 4" LCD Rider Information Center: User Selectable Blue/Red Backlighting & Brightness, Programmable Service Intervals, |
| | Speedometer, Tachometer, Odometer, Tripmeter, Clock, Hour Meter, Gear Indicator, Fuel Gauge, Coolant Temperature, Voltmeter, Service Indicator and Codes, Seat Belt Reminder, DC Outlet |
| Lighting | Halogen Headlamps, 55W low beam, 60W high beam, LED Taillamps |
| Other Standard Features | Premium Cut & Sew Seats, Polaris Pulse Electrical System (3 position), Standard In-Dash SAE Charge Port |
| Tilt Steering | Standard |
| | |

Tires / Wheels

| Front Tires | 25 x 8-12; Carlisle 489 |
|-----------------|--------------------------|
| Rear Tires | 25 x 10-12; Carlisle 489 |
| Tire Ply Rating | 4 Ply Rated |
| Wheels | 12" Black Aluminum |

Suspension

| Front Suspension | MacPherson Strut 9 in (22.9 cm) Travel |
|------------------|--|
| Rear Suspension | Dual A-Arm, IRS 10 in (25.4 cm) Travel |
| Turning Radius | 12.7 ft |